



TRIDENT WIDE BRAKE PEDAL for GL 1800

4077

PARTS INCLUDED

- 1 Trident Wide Brake Pedal with Chrome Arm
- 1 Installation Instructions

Please read and understand entire instructions before starting installation.

THANK YOU FOR CHOOSING KÜRYAKYN!

IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND NOTICES REGARDING THE USE AND CARE OF THIS PRODUCT.

WARNING

THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

NOTICE

This indication alerts you to the fact that ignoring the contents described herein may negatively affect product performance and functionality.

NOTICE

IF INSTALLING THIS PRODUCT FOR ANOTHER PARTY, PLEASE MAKE SURE THEY RECEIVE THIS COPY OF THE INSTALLATION INSTRUCTIONS SO THEY ARE AWARE OF THE IMPORTANT INFORMATION CONTAINED IN THEM.

TOOLS SUGGESTED

Set of Metric Combination Wrenches, Set of Metric Hex Wrenches, Large Flat Blade Screwdriver, FT/LBS Torque Wrench and Metric Hex Sockets

STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.

STEP 1

Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition. Let cool.

NOTE: The larger than stock brake pedal pad on the Trident Brake Pedal may provide easier braking. The larger pad may change the amount of pressure needed on the pedal in any given braking situation. Familiarize yourself with the larger pad and amount of pressure needed.

WARNING

YOU WILL BE WORKING AROUND THE ENGINE AND EXHAUST SYSTEM DURING INSTALLATION. ENSURE THAT THE ENGINE AND EXHAUST SYSTEM HAVE FULLY COOLED TO PREVENT INJURY.

CUSTOMER SERVICE

877.370.3604 (toll free)

INSTALLATION QUESTIONS

techsupport@kuryakyn.com
or call 715.247.2983

LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
 - The product must be properly installed, maintained and operated under normal conditions.
 - Kuryakyn makes no warranty, expressed or implied, with respect to any gold plated products.
 - Kuryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn and a customer.
- Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
- Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. L.E.D.'S contained in components of Kuryakyn products will be warranted for defects in materials and workmanship for 3 years from the date of purchase where as all other components shall be warranted for one(1) year. This includes, but is not limited to; control modules, wiring, chrome & other components.
- Kuryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Kuryakyn. Kuryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

ABOUT OUR CATALOG

For purchasing Kuryakyn® products, you can receive a complete catalog free of charge. Send the Proof-of-Purchase below with your address to: Kuryakyn, P.O. Box 339, Somerset, WI 54025. Please indicate either Accessories Catalog for Harley-Davidson® or GL & Metric Cruisers.

Be sure to ask your local dealer about other Kuryakyn® products, the motorcycle parts and accessories designed for riders by riders.

©2005 Kuryakyn USA® All Rights reserved.



-cont.-

4077-21GL-0513

kuryakyn.com

NOTE: Marking a line on the splined brake shaft that lines up with the split in the brake arm before beginning will give you a starting point for placement of the new Trident Brake Pedal. **PIC 1**

STEP 2 Remove the two hex fasteners that secure the footrest mount on the brake side. Remove the mount. Loosen the pinch bolt on the stock brake lever. **PIC 1** Set these aside, they will be reused.

STEP 3 Remove the stock brake lever from its splined mount. If this is difficult, it may help to carefully wedge a screwdriver in the pinch slot where the pinch bolt was removed. **PIC 1** and **PIC 2**

STEP 4 Line up the seam in the new Trident Brake Pedal with the mark, and install the new lever to the brake shaft. **PIC 3** Install the new lever in the same orientation as the original.

NOTE: It may be necessary to reach in behind the splined brake control shaft with your finger, or a long screwdriver and hold the shaft in place while installing the new brake lever.

STEP 5 Sit on the bike and confirm that the new lever is positioned to your liking. If not, remove it and rotate it on the splines by one or two teeth and reinstall. Secure the lever in place with the stock pinch bolt (Anti-seize should be applied to these threads.) removed in Step 2.

⚠ WARNING ENSURE THE NEW BRAKE PEDAL IS POSITIONED TO ALLOW FULL APPLICATION OF THE BRAKES WHEN NEEDED. FAILURE TO PROPERLY POSITION THE BRAKE PEDAL MAY CAUSE LOSS OF CONTROL RESULTING IN SERIOUS INJURY OR DEATH.

STEP 6 Replace the footrest mount that was removed in Step 2 with the removed fasteners. **PIC 4** Place a drop of Blue Loctite on the threads of each fastener and **torque to 20 FT/LBS.**

⚠ WARNING IT IS THE INSTALLERS RESPONSIBILITY TO TEST THE TRIDENT BRAKE PEDAL WITH CHROME ARM FOR PROPER FUNCTION BEFORE OPERATING THE MOTORCYCLE. IMPROPER BRAKE PEDAL/ARM FUNCTION MAY CAUSE LOSS OF CONTROL RESULTING IN SERIOUS INJURY OR DEATH.

NOTICE It is the installer's responsibility to ensure that all of the fasteners (including pre-assembled) are tightened before operation of the motorcycle. Küryakyn will not provide warranty coverage on products or components lost due to improper installation or lack of maintenance. Periodic inspection and maintenance are required on all fasteners.

